

CONTINUON™ C1221

Turnkey Compute Farm Platform



The C1221 is the first I-Bus enclosure to support up to 20x IBC2802 CPU boards

Ordering Information

C1221

12U, 20-slot CPCI enclosure

Power Subsystem Options

PSU-AC

Four 300W N+1 AC power supplies

PSU-DC

Four 300W N+1 -48VDC power supplies

Control & Monitoring Options

IBC-2501

Chassis Management Controller, IPMI v.1.0 compliant Module.



Specifications

Dimensions

- 12U Height
- 21" x 17.1" x 12" (hwd)
- 634 x 434 x 304 mm

Enclosure

- 20-slot card area
- 6 SCA SCSI drive bays
- 4 power supplies
- 2 Rear power input bays
- ESD grounding locations (front & rear)
- Alarm panel used with optional Chassis Management Controller (CMC)
- Front DC power switch
- Designed to meet NEBS/ETSI standards

Systems

- Available as systems using:
- IBC 2600, 2601 & 2801 PIII based SBCs
 - CP 1500, 20xx SPARC based SBC
 - Windows NT & 2000, Solaris and Linux operating systems

Backplane

- Supports one-slot system master (slot#1)
- 19 full hot-swap I/O slots
- 20-slot continuous H.110 backplane
- Dual power input connectors

Fail-Safe OPTICOOL™ Cooling

- push-mix-pull cooling technology
- 6 fan, hot-swap cooling array in air intake
- Patented air flow mixing and directing tray
- 4 individually hot-swap blowers exhaust
- Optional blower and fan speed control with I-Bus CMC

Power Supply Subsystem

- Four Hot-swap redundant power supplies
- N+1 Redundant (N=3) 300W supplies
- Input Voltage: 90-132/180-250 VAC auto-ranging, Optional -48VDC
- Output Power: +3.3V@30A, +5V@25A, +12V@6A, -12V@0.5A (each supply)
- Combined power of +5 and +3.3V not to exceed 35A total per supply

Operating Environment

- Temperature: 0 to 40° C
- Humidity: 5% to 85% @40°C (non-condensing)
- Shock: 10g @11mS
- Vibration: 0.25G @2-100Hz, 1.5g@100-500Hz

Standards Compliance

- PICMG 2.0 R 3.0, PICMG 2.1 R 2.0, PICMG 2.5 R 1.0, PICMG 2.9 R1.0, PICMG 2.10 R 1.0, PICMG 2.11 R 1.0,
- ESD: CE
- EMI: CE, FCC, UL/CUL
- Safety: UL/CUL, CE, CB
- NEBS

Maintaining
high performance
virtually forever


Presenting High Availability and beyond...

99.9999%
availability

The state-of-the-art C1221 CompactPCI platform is the highest density CompactPCI based 19" rack system platform on the market today, and the first to employ I-Bus patented Fail-Safe OptiCool™ technology. In 12U of space, the C1221 boasts high availability features to cater to the "five nines" requirements of the communications, network, broadcast and medical OEM. All critical modules on the C1221 are easily accessible and fully hot-swap. The C1221 supports full I/O card hot-swap to PICMG 2.1 R2.0 and N+1 redundant hot-swap power supplies.

In high density computing platform the most critical component is the cooling. I-Bus continues to lead the CompactPCI market with the patented Fail-Safe OptiCool™ method of push-mix-pull cooling. Fail-Safe Opticool incorporates a unique lower hot-swap fan array that takes advantage of the axial direction of the fans to most efficiently pressurize the air at the bottom of the chassis. The unique mixing tray can be tuned to mix the intake air, redirect the air upward and distribute the air to where it is needed most, even in the event of a single fan failure. To direct the air through the cards and power supplies, three individually hot-swap blowers pull the low pressure air upward and direct it toward the rear of the chassis. Optimization of cooling, noise and blower life expectancy is achieved with the addition of the optional I-Bus Chassis Management Controller (CMC), which provides independent speed control for the individual blowers and the fan array. The CMC is added in its dedicated slot at the rear of the chassis.

With all of these high-availability features, the C1221 excels in applications requiring small size, optimal cooling, high density and the highest levels of reliability, ensuring the greatest level of application availability. Additional features include a 20-slot CPC/H.110 backplane, full rear I/O module support, front to back airflow, NEBS compliance and the I-Bus standard warranty. Combine the C1221 with the IBC series of award winning single board computers, fully compliant PICMG 2.12 R1.0 hot-swap middleware, Linux, Solaris and Windows HA middleware as well as our extensive list of third party application cards for a truly Turnkey Compute Farm Platform.



For Further Information



Worldwide Headquarters

I-Bus Corporation
3350 Scott Blvd, Building 54
Santa Clara, CA 95054
United States
Phone : +1 (408) 450-7880
Fax : +1 (408) 450-7881
Toll Free: 877-777-IBUS
Email: contact.us@ibus.com

European Headquarters

I-Bus UK Ltd
Unit 6, Chichester Business Park
City Fields Way, Tangmere
West Sussex, PO20 2LB, UK
Tel: +44 (0) 1243 756300
Fax: +44 (0) 1243 756301
Email: contact.uk@ibus.com

France, Italy

I-Bus France
B.P 45 Valbonne
06901 Sophia Antipolis CEDEX
France
Tel: +33 (0) 493 004 360
Fax: +33 (0) 493 004 369
Email: contact.fr@ibus.com